

B770A WHEEL FELLER BUNCHER



SOLID STABILITY & EXCELLENT RIDE.

The transverse mounted engine, low center of gravity, and wider axles provide rock solid stability. The cab sits between the axles instead of close to the front frame, delivering a topnotch ride for the operator. Improved foot pedal angles and 2 inches more leg room enhances operator comfort.



IMPROVED TRAVEL.

Higher ratio axles reduce the torque in the drive train by almost 40%. The improved axle ratio also creates 5% more drawbar power and 10% more ground speed in turtle mode. Fully adjustable speed settings let the operator set working ranges and bump through the ranges during operation.



SYSTEM SIMPLIFICATION.

Simplified electrical and hydraulic systems, fewer electrical pin connections and sensors, and an overall reduction in hoses and fittings maximize reliability. Improved front frame reduces damage to lift cylinder hoses, provides access to hoses through a removable guard, and reduces debris entry.



CAB DURABILITY.

The cab features integrated LED lights, removing the light boxes from the previous series. 1.7x thicker skylight with cross bars removed provides an unobstructed view to tree tops. The new roof angle deflects debris more efficiently and has an overall thicker cab roof for durability.



SAW CIRCUIT RELIABILITY.

An optimized high performance saw circuit, that includes a dedicated saw valve results in more power, efficiency, and quicker saw recovery speeds. Case drain filtration adds an additional level of protection and confidence to the system. Priority settings allow the control system to deliver saw recovery or propel to match the application.



EXCELLENT SERVICEABILITY.

Pressurized engine compartment keeps debris out of the machine reducing cleaning. The sloped hood sheds debris to prevent build up. Ground level fuel fill, electric hydraulic oil fill pump, and excellent engine access deliver superior serviceability making it quick and easy to do daily maintenance.



B770A SPECIFICATIONS

ENGINE MODEL	Cat® C7.1 Stage 5	WHEELBASE	115" 2921mm	GROUND CLEARANCE	19.4" 493 mm
GROSS POWER	302 hp 225 kW	FUEL CAPACITY	81.6 gal 309 L	TRANSPORT WIDTH	9' 1" 3.03 m
ENGINE SPEED	1880 rpm	DEF CAPACITY	5.0 gal 19 L	TRANSPORT HEIGHT	10' 11" 3.33 m
WEIGHT	39,656 lb 17 988 kg	HYDRAULIC SYSTEM	71.1 gal 269 L	TRANSPORT LENGTH	25' 4" 7.73 m

FELLING SAWS SPECIFICATIONS

ACCUMULATION AREA	8.6 ft² 0.80 m²
MAX SINGLE CUT	23.0" 584 mm
WEIGHT	6,275 lb 2846 kg

BH230 BUNCHING SAW

GP230 CENTER POST

5.1 ft² 0.47 m²
23.0" 584 mm
7,100 lb 3220 kg

GP230 GENERAL PURPOSE

5.8 ft² 0.54 m²
23.0" 584 mm
6,150 lb 2790 kg

Base configuration includes 30.5-32 26PR Tires, BH230 bunching saw, and full tank of fuel. Weight deduct 1,720 lb (780 kg) for 28L-26 tires, add 840 lb (381 kg) for 30.5L-32 2X Ring tires, and 0 lb (0 kg) for 67-34 tires. Height and ground clearance deduct 4.0" (10.2 cm) for 28L-26 tires, 2.9" (7.4 cm) for 67-34 tires.

POWERTRAIN

- Cat® C7.1 engine certified to EPA Stage 5
- Primary and secondary fuel filters, including water separator
- Electric fuel priming and transfer pump
- Centrifugal engine air pre-cleaner
- 2-Stage engine air cleaner
- Cross-flow cooling system w/side by side cores including a/c and fuel cooler
- Hydraulic on demand reversing cooling fan
- Electronic reversing pressurizing fan
- 2-Speed, hydraulically shifted transmission
- New higher ratio axles
- Momentary front differential lock
- On/off rear differential lock
- Heavy-duty driveshafts
- Lubed for life universal joints except center joint
- Spring applied, hydraulically released parking brake

OPERATOR ENVIRONMENT

- Enclosed OPS/FOPS/ROPS certified tilt cab with increased roof thickness
- Unobstructed skylight
- Reverse slope 3-piece windshield
- Slider windows & door screens
- High capacity HVAC system
- Pressurized water tank in rear of machine
- Air suspension seat with harness seat belt
- Joystick steering controls
- Adjustable operator controls
- Weiler machine software
- Terrain selection mode
- Road steer mode
- 6 speed selections
- Joystick gather arm(s) controls
- AM/FM/Bluetooth radio
- 24V to 12V converter, 1 x 12V power port, and 1 x USB port
- 2 beverage holders

HYDRAULICS

- Weiler software monitors performance and delivers power where needed
- Variable displacement pumps with load-sense hydraulics
- Oversized in-tank filter
- High performance saw circuit with case drain filter
- Electric hydraulic oil fill pump

ELECTRICAL

- 24-volt electrical system with 2 x 12-volt batteries
- Main disconnect switch with Diesel Exhaust Fluid (DEF) purge indicator light
- 2 x front and 2 x rear LED working lights integrated into the cab
- Product Link™ Ready

OTHER STANDARD EQUIPMENT

- Double walled box section frames to support bending and twisting forces
- Field proven dual tapered roller bearing upper and lower center hitch
- Pressurized engine, hydraulic, and Clean Emission Module compartments
- Ground level fuel fill with right hand DEF fill
- Single side engine service

OPTIONAL EQUIPMENT

- Cab Sweeps
- Foot Rest
- Skylight Sunshade
- CB Radio
- Phone Holder
- Product Link™ (PL243 Cellular or PL631 Satellite)
- Rear-view Camera w/ 10" Monitor & 2 x Rear & 2 x Front LED Lights
- Fire Extinguisher
- Water Tank Fill w/ RV Antifreeze Mixture (good to -12 deg F)
- Saw Speed Sensor
- Carbide or Steel Cutting Teeth
- 28L-26 Tires - Overall Width 117" (2.97 m)
- 30.5L-32 Tires - Overall Width 119" (3.03 m)
- 30.5L-32 2XRing Tires or 2XRing Front Only - Overall Width 119" (3.03 m)
- 67-34 Tires - Overall Width 129" (3.27 m)
- 73x44-32 - Overall Width 147" (3.74 m)

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry dealers worldwide.

WARRANTY

12 months standard. Extended warranty available.

